

FORMENTERA CTFS

FORMENTERA CTN



➤ Touch screen user interface

➤ Ready for connection to an external probe (optional)

➤ 26-plate DHW heat exchanger

➤ Controls to manage three different types of solar thermal systems fitted as standard (solar probe is optional)

➤ Boiler hydraulic replacement kit

Available heat outputs:

CTFS
24
kW

CTFS
28
kW

CTFS
32
kW

CTN
24
kW

CTN
28
kW

Pre-set to run on Methane or LPG



WALL-HUNG COMBI BOILERS



- Mono-thermal heat exchanger
- 26-plate stainless steel DHW heat exchanger
- 3-speed pump with integrated air purging device
- Integrated hydraulic assembly including: three-way valve, automatic by-pass, safety valve, pressure transducer, unloading tap, connection to the expansion vessel
- Integrated safety and modulation electronic board
- Installation flexibility thanks to IPX5D electrical protection degree
- Multifunctional relay for connection to systems with zone valves or to solar systems or to remote boiler shutdown alarms
- Virtual room temperature control with weather compensation via external temperature probe (option)
- Management of high-and low-temperature heating zones via electric board (option)
- Energy efficiency marking (92/42/EC)

CTFS:★★★ CTN:★★

Model	Type of gas	Code	Heat output kW	Efficiency at nominal heat output	Gross weight (kg)
FORMENTERA CTFS 24 <i>sealed chamber</i>	METHANE	CFNxx2CA24	23.7	93.0 %	37.50
	LPG	CFNxx3CA24			
FORMENTERA CTFS 28 <i>sealed chamber</i>	METHANE	CFNxx2CA28	28.6	93.7 %	38.00
	LPG	CFNxx3CA28			
FORMENTERA CTFS 32 <i>sealed chamber</i>	METHANE	CFNxx2CA32	30.8	93.4 %	38.50
	LPG	CFNxx3CA32			
FORMENTERA CTN 24 <i>open chamber</i>	METHANE	CFNxx2CC24	23.1	90.6 %	36.00
	LPG	CFNxx3CC24			
FORMENTERA CTN 28 <i>open chamber</i>	METHANE	CFNxx2CC28	27.4	90.0 %	36.50
	LPG	CFNxx3CC28			

INCLUDED IN THE PRICE: standard hydraulic kit, paper template, flue gas discharge diaphragm and air-intake blanking taps kit

FORMENTERA RTFS

FORMENTERA RTN



- Touch screen user interface
- Ready for connection to an external probe (optional)
- 26-plate DHW heat exchanger
- Control of 2 heating zones via two temperature probes and 0KITZONE05 (optionals)
- Boiler hydraulic replacement kit

Available heat outputs:

RTFS
24
kW

RTFS
28
kW

RTFS
32
kW

RTN
24
kW

RTN
28
kW

Pre-set to run on Methane or LPG



HEAT ONLY WALL-HUNG BOILERS



- Mono-thermal heat exchanger
- 26-plate stainless steel DHW heat exchanger
- 3-speed pump with integrated air purging device
- Integrated hydraulic assembly including: automatic by-pass, safety valve, pressure transducer, unloading tap, connection to the expansion vessel
- Integrated safety and modulation electronic board
- Installation flexibility thanks to IPX5D electrical protection degree
- Multifunctional relay for connection to systems with zone valves or to solar systems or to remote boiler shutdown alarms
- Virtual room temperature control with weather compensation via external temperature probe (option)
- Management of high- and low-temperature heating zones via electric board (option)
- Energy efficiency marking (92/42/EC)
RTFS: ★★★ RTN: ★★

Model	Type of gas	Code	Heat output kW	Efficiency at nominal heat output	Gross weight (KG.)
FORMENTERA RTFS 24 <i>sealed chamber</i>	METHANE	CFNxx2RA24	23.7	93 %	35.50
	LPG	CFNxx3RA24			
FORMENTERA RTFS 28 <i>sealed chamber</i>	METHANE	CFNxx2RA28	28.6	93,7 %	36.50
	LPG	CFNxx3RA28			
FORMENTERA RTFS 32 <i>sealed chamber</i>	METHANE	CFNxx2RA32	30.8	93.4 %	37.00
	LPG	CFNxx3RA32			
FORMENTERA RTN 24 <i>open chamber</i>	METHANE	CFNxx2RC24	23.1	90.6 %	34.50
	LPG	CFNxx3RC24			
FORMENTERA RTN 28 <i>open chamber</i>	METHANE	CFNxx2RC28	27.4	90.0 %	35.00
	LPG	CFNxx3RC28			

INCLUDED IN THE PRICE: standard hydraulic kit, paper template, flue gas discharge diaphragm and air-intake blanking taps kit